



COMBINATION SAFETY SHOWERS AND EYE/FACE WASH

ESSENTIAL RANGE

Item Code	Description
H-D5016	FLOOR MOUNTED GALVANISED POWDER COATED RAL6029 GREEN EMERGENCY SAFETY SHOWER WITH 304 STAINLESS-STEEL EYE/FACE WASH UNIT POLY SIGN AND GRP SPRAY NOZZLE (NO BOWL, DRAIN ASSEMBLY, NO FOOT TREADLE, NO ABS SHROUD)

The Essential Range of Safety Shower and Eye/Face Wash, perfect for environments where freezing or overheating is not a concern. Engineered to deliver ANSI 358.1-2014 standard flow rates, ensuring a robust flow of 76 Liters per minute of potable water from the shower and 12 Liters per minute to the eye/face wash.

SPECIFICATIONS

OPERATING PRESSURE	2.0 to 6 BAR G (29 to 87 PSI)
MINIMUM FLOW AT OPERATING PRESSURE	Shower: 76 litres/minute minimum (20 US Gallons). Eye/face wash: 12 litres/minute minimum (3 US Gallons)
MINIMUM AMBIENT OPERATING TEMPERATURE	5° C (41° F)
MAXIMUM AMBIENT OPERATING TEMPERATURE	35° C (95° F)

OPTIONAL EXTRA ATTACHMENTS

Item Code	Description
H-DA002	BOWL AND DRAIN ASSEMBLY FOR GALVANISED COMBINATION SAFETY SHOWER AND EYE/FACE WASH SUITS H-D5016
H-DA003	GRP RED FOOT CONTROL PANEL ASSEMBLY FOR EYE FACE WASH ACTIVATION SUITS H-D5016, H-D5017 & H-D5020
H-DA004	ADDITIONAL ROSE / ABS SHROUD COVER FOR DRENCH SHOWER SUITS H-D5016 & H-D5017 - GRP SPRAY NOZZLE REMAINS



Shown with optional eye/facewash bowl (Part No. H-DA002) and foot treadle (Part no. H-DA003)



Shown with optional eye/facewash bowl (Part No. H-DA002), foot treadle (Part no. H-DA003) and ABS shroud cover over spray nozzle (Part no. H-DA004)

