

# SELF-CONTAINED GRAVITY FED EYEWASH

## FEATURES

- A wall or bench mounted, self-contained eye wash unit providing 15 minutes of water flow (Exceeds 15mins for H-P401)
- Emergency First-Aid water treatment for work sites without plumbing capabilities
- Large filling cap makes for easy filling, cleaning and inspection whilst the retractable tray protects against airborne contaminants
- High visibility colour provides quicker identification for a casualty in distress
- Meets ANSI and EN standards
- Test weekly for compliance of ANSI Z 358.1-2014 – Water Preservative Concentrate – Refer Page 65

## MATERIALS OF CONSTRUCTION

MAIN BODY AND PULL DOWN	High density polyethylene
WALL BRACKET	Galvanised mild steel
NOZZLES	Polypropylene
STANDARD FINISH	H-P400 - Green and Orange H-P401 - Yellow and Green
WATER CAPACITY	H-P400 - 34 litres H-P401 - 81 litres
MINIMUM FLOW	1.5 litres/minute minimum (0.4 US Gallons) (H-P401 Exceeds)
MINIMUM AMBIENT OPERATING TEMPERATURE	5° C (41° F)
MAXIMUM AMBIENT OPERATING TEMPERATURE	35° C (95° F)
EYE/FACE WASH OPERATION	Pull Down Tray for Activation
DIMENSIONS (WxDxH)	H-P400 - 580mm x 250mm x 400mm Packed H-P401 - 610mm x 610mm x 660mm Packed
WEIGHT (NO OPTIONS)	H-P400 - 4kg Net / 5kg Packed H-P401 - 8.2kg Net / 10kg Packed

## SELF-CONTAINED EYEWASH

Item Code	Description
H-P400	Portable Gravity Fed Eyewash 34L – Wall Mount Only
H-P401	Portable Gravity Fed Eyewash 81L – Wall / Bench Mount
H-P400TJ	Thermal Protection Jacket for H-P400 (34L)

